

FLAMMABILITY TEST CERTIFICATE - 86575

COMPANY DETAILS: SMD CONTRACTS

SMD GROUP LTD, UNIT F2, PITTMAN WAY, FULWOOD,

PRESTON, PR2 9ZD

CONTACT NAME(S):

TEL: 01772665263

EMAIL:

 DATE RECEIVED:
 16/12/2020

 DATE TESTED:
 17/11/2020

 DATE ISSUED:
 18/11/2020

 PO NUMBER:
 NOT STATED

SAMPLE DESCRIPTION: CONWAY HERRINGBONE DRAPERY

COLOUR: GREY

QUALITY/BATCH REF: NOT STATED MODEL REF: NOT STATED

COMPOSITION: 90% IFR AND 10% NON IFR END USE: CONTRACT DRAPERY

DESCRIPTION OF WEAVE:NOT STATEDMASS PER UNIT AREA:NOT STATEDFR TREATMENT:NOT STATEDMANUFACTURER:NOT STATEDSUPPLIER:SMD CONTRACTS

SPECIFICATION/REQUIRMENT:

IMO FTP Part 7: 2010 – Test for vertically supported textiles and films.

PRE-TREATMENT:

No wetting procedure had been carried out. The results obtained in this report relate only to the tested specimens as received.

CONDITIONING:

The specimens had been conditioned for at least 24 hrs in a specified atmosphere at $20 \pm 5^{\circ}$ C and $65 \pm 5\%$ r h.

Authorised By:

Zeb Alam
Operations Director

Mark Jones Quality Manager Karen Brooks

Managing Director







FLAMMABILITY TEST CERTIFICATE - 86575

TEST RESULTS BEFORE WASH – FACE SIDE:

Test Results (Warp)	1	2	3	4	5
Application Time (as determined by pre-testing):	15s (FACE)				
After Flame time:	0.00	0.00	0.00	0.00	0.00
Flame reached an edge:	NO	NO	NO	NO	NO
Charred Length: (mm)	65	69	63	64	64
Ignition of Cotton Wool (Y/N)	NO	NO	NO	NO	NO
Occurrence of surface flash (Y/N)	NO	NO	NO	NO	NO
Specimen Result:	PASS	PASS	PASS	PASS	PASS

Test Results (Weft)	1	2	3	4	5
Application Time (as determined by pre-testing):	15s (FACE)				
After Flame time:	0.00	0.00	0.00	0.00	0.00
Flame reached an edge:	NO	NO	NO	NO	NO
Charred Length: (mm)	65	55	53	50	55
Ignition of Cotton Wool (Y/N)	NO	NO	NO	NO	NO
Occurrence of surface flash (Y/N)	NO	NO	NO	NO	NO
Specimen Result:	PASS	PASS	PASS	PASS	PASS

^{*}after flame time ≤5s for any specimen.

CONCLUSION:

The sample supplied meets the performance criteria as stated in paragraph 3 of IMO FTP Part 7: 2010.



^{*}no flame propagation to the edges for any specimen.

^{*}no ignition of the cotton wool for any specimen.

^{*}average char length ≤ 150mm.

^{*}no occurrence of surface flash more than 100mm from the point of ignition