

Our Ref: SW/RM

<u>Page 1 of 2</u>

SMD Contracts Limited Unit F2 Pittman Way Fulwood Preston PR2 9ZD

Contact: Tracey O'Gara; Emma Lockwood; Sarah West

DATE RECEIVED : 2 MAR 2020

FABRIC SUPPLIER : SMD

QUALITY/REFERENCE : SHETLAND

REPUTED FIBRE CONTENT : 100% POLYESTER

FABRIC DESCRIPTION : WOVEN

COLOUR/DESIGN : BUTTERSCOTCH

END USE : CONTRACT UPHOLSTERY

PERFORMANCE STANDARD : BS2543:2004 & BSEN 14465:2003 + A1:2006

REPORT SUMMARY

Tests	Method	Pass	Fail	Requirement
Determination of Sulphur	BS 3424-19:1989 22A			No requirement
Staining	Determination of Sulphur			
	Staining			
Abrasion of upholstery	Abrasion Resistance BS EN	Pass		Level A suitable for Any End
	ISO 12947-2: 1998 / BS EN			Use
	14465: 2003 Annex A			



This report may not be reproduced except in full without the written approval of HSTTS. In all circumstances results of tests are implied as referring only to the sample supplied and should not be construed or interpreted on any other basis. The comments given in the report are for guidance only and are not a part of the results. Where specified in a test method, preconditioning in accordance with ISO 139 is not carried out as samples are exposed to the conditioning atmosphere specified within ISO 139 for a minimum of 16 hours prior to test.





10 March 2020

Report 360241 Page 2 of 2

COLOUR FASTNESS TO:

BS 3424-19:1989 22A Determination of Sulphur Staining *

Immediately after test Grade 4 Temporary Staining

After 24 Hours Grade 4-5 Stained

Requirement:

PHYSICAL

Abrasion Resistance BS EN ISO 12947-2: 1998 / BS EN 14465: 2003 Annex A ~ Requirement:

12 kPa load.

Number of rubs to breakdown:	
Head 1 100,000+	
Head 2 100,000+	
Head 3 100,000+	
Head 4 100,000+	
Shade change after 3,000 rubs:	4-5

Level A suitable for Any End Use

Tests indicated * are non-UKAS accredited.

Tests indicated § are within the bounds of the flexible scope of accreditation operated by the laboratory.

